

# INSTALLATION INSTRUCTIONS

## DRAG SPECIALTIES SEATS FOR 2000-UP SOFTAIL

**ATTENTION INSTALLER** (if other than owner): Please forward this instruction sheet to the purchaser of this product. These instructions contain valuable information necessary to the end user.

**INTRODUCTION:** These instructions describe the procedure for properly installing Drag seats onto FXST™ models.

Review instructions carefully before beginning, as they contain important information. Please retain for future reference.

Particularly important information is distinguished in these instructions by the following notations:

**NOTE:** A NOTE provides key information to make procedures easier or clearer.

**CAUTION:** A CAUTION indicates special procedures that must be followed to avoid damage to the motorcycle and/or accessories.

**WARNING!:** A WARNING indicates special procedures that must be followed to avoid injury to a motorcycle operator or person inspecting or repairing the motorcycle.

### MOUNTING HARDWARE

*490015A	Bracket	1
*424130	Screw	2
* = Mounted on seat		

### PROCEDURE:

1. Begin by placing the bike on the side stand.
2. Remove the stock seat from the bike.
3. The rear bracket comes installed on seat.
4. Slip your new seat over the tab at the front of the frame near the gas tank and position on the rear fender.
5. Center rear of seat in relation toissy bar and fender.
6. With seat centered, position rear bracket to line up with hole in fender. Remove seat and tighten the fasteners holding the bracket.

**CAUTION:** Review your mounting kit, verify the correct thread pitch in your application and use the appropriate stud.

7. Slip the seat onto the front frame tab and attach the rear bracket to the fender.

FXST™ is a registered trademark of Harley-Davidson Motor Company, Inc., Milwaukee, WI, U.S.A.



## DRAG SPECIALTIES

3511 Kennedy Road, Janesville, WI 53545  
010001